



**TRANSPORT DES MARCHANDISES DANGEREUSES
CERTIFICAT D'AGREMENT DE TYPE D'EMBALLAGE**

Applicant : CARTOSPE PACKAGING
13, voie Industrielle
60350 ATTICHY FRANCE

**N° 7018
Indice 3**

REFERENCE DOCUMENTS :

Site of conditioning :
Non applicable

- Road transport : ADR (Part 6), to date in 01/01/2019
- Rail transport : RID (Part 6), to date in 01/01/2019
- Transport by waterway : ADN (Part 6), to date in 01/01/2019
- Maritime transport : IMDG code (Part 6), to date in 01/01/2019
- Air transport : Doc OACI 9284 AN/905 (Part 6), to date in 2017/2019
- UN Recommendations on the transport of dangerous goods - Model Regulations - ST/SG/AC.10/1/Rev.20 - Part 6

DESCRIPTION OF THE TYPE OF PACKAGING (according to information given by the applicant) :

Sample record n° 11755

- Manufacturer : CARTOSPE PACKAGING , F-60350 Attichy
- Packaging code : 4G
- Type, materials : Caisse , Carton
- Construction method : Collage
- Commercial reference : 12 LVERSION 2010
- Constituent raw material : Carton ondulé DF, Kraft blanc 125 g/m² / Recyclé 120 g/m² / Test 170 g/m², cannelure B, 1.1 selon NF Q 12-008, indice Cobb < 155 g/m²/30'

- Drawings : ft 13986 du 15/12/2009
- Empty weight (tare) : 0,235 kg
- Overall external dimensions : 0,206 x 0,206 x 0,31 m
- Internal dimensions : 0,200 x 200 x 0,302 m
- Minimum thickness : 2,42 mm
- Closures : Rabats supérieurs recouvrants avec languette de fermeture verrouillable

- Handling : 2 poignées prédécoupées sur deux faces opposées en partie haute
- Particularities : Fond automatique.

Inner arrangement : Lest constitué de granulés PE dans une sachepastique (épaisseur 40 µm, dimensions 434 x 655 mm) collée sur les parois intérieures de la caisse (en partie supérieure) et fermée par un lien plastique coulissant incorporé dans la sachepastique (chignon noué)

AUTHORIZED AREAS OF USE : Dangerous goods solides in the following conditions :

- Packaging group : II,III
- Max. gross weight : 4 kg
- Stacking : Maximal Load : 35 kg

TEST AND MARKING :

Satisfactory test results, according to report : **BVT 172735 indice 1 du 15/01/2010**

Quality assurance plan reference and index : **PAQ 1727-7F-8F-830 indice 1**

Marking model to be placed on the condition that the regulatory measures are met



4G / Y 4 / S / - - *

F / BVT 172735 / CARTOSPE PACKAGING

* See the appendix to the approval certificate

The French text serves as a basis for the translation, and should any difference exist between the French text and a text in another language, the French text will prevail.

Issued in Rungis

Manager of the approved test laboratory

On 24/04/2019 for a period of five years

Mrs E.FRAGU

A copy of this report is sent to the Ministry of Transport.

**TRANSPORT DES MARCHANDISES DANGEREUSES
CERTIFICAT D'AGREMENT DE TYPE D'EMBALLAGE**

Applicant : CARTOSPE PACKAGING
13, voie Industrielle
60350 ATTICHY FRANCE

**N° 6783
Indice 3**

REFERENCE DOCUMENTS :

- Road transport : ADR (Part 6), to date in 01/01/2019
- Rail transport : RID (Part 6), to date in 01/01/2019
- Transport by waterway : ADN (Part 6), to date in 01/01/2019
- Maritime transport : IMDG code (Part 6), to date in 01/01/2019
- Air transport : Doc OACI 9284 AN/905 (Part 6), to date in 2017/2019
- UN Recommendations on the transport of dangerous goods - Model Regulations - ST/SG/AC.10/1/Rev.20 - Part 6

Site of conditioning :
Non applicable

DESCRIPTION OF THE TYPE OF PACKAGING (according to information given by the applicant) :

- Manufacturer : CARTOSPE PACKAGING , F-60350 Attichy
 - Packaging code : 4G
 - Type, materials : Caisse , Carton
 - Construction method : Collage
 - Commercial reference : 25 L VERSION 2010
 - Constituent raw material : Carton ondulé DF, Kraft blanc 125 g/m² / Recyclé 120 g/m² / Test 170 g/m², cannelure B, 1.1 selon NF Q 12-008, indice Cobb < 155 g/m²/30'
 - Drawings : ft 13985 du 15/12/2009
 - Empty weight (tare) : 0,35 kg
 - Overall external dimensions : 0,236 x 0,236 x 0,44 m
 - Internal dimensions : 0,230 x 0,230 x 0,43 m
 - Minimum thickness : 2,42 mm
 - Closures : Rabats supérieurs recouvrants avec languette de fermeture verrouillable
 - Handling : 2 poignées prédécoupées sur deux faces opposées en partie haute
 - Particularities : Fond automatique.
- Inner arrangement :** Lest constitué de Granulés PE dans une sachette plastique (épaisseur 40 µm, dimensions 0,492 x 0,860 m) collée sur les parois intérieures de la caisse (en partie supérieure) et fermée par un lien coulissant incorporé dans la sachette (chignon noué).

AUTHORIZED AREAS OF USE : Dangerous goods solides in the following conditions :

- Packaging group : II,III
- Max. gross weight : 12 kg
- Stacking : Maximal Load : 70 kg

TEST AND MARKING :

Satisfactory test results, according to report : **BVT 172734 indice 1 du 15/01/2010**

Quality assurance plan reference and index : **PAQ 1727-7F-8F-830 indice 1**

Marking model to be placed on the condition that the regulatory measures are met



4G / Y 12 / S / - - *

F / BVT 172734 / CARTOSPE PACKAGING

*** See the appendix to the approval certificate**

The French text serves as a basis for the translation, and should any difference exist between the French text and a text in another language, the French text will prevail.

Issued in Rungis

Manager of the approved test laboratory

On 24/04/2019 for a period of five years

Mrs E.FRAGU

A copy of this report is sent to the Ministry of Transport.

Ministère chargé des transports terrestres et maritime de matières dangereuses



Bureau de Vérifications Techniques
36 rue du Jura
CS 10398
94633 RUNGIS CEDEX
FRANCE
Tél. +33 (0)1 41 80 59 00

S.A.S au capital de 282 150 € RCS CRETEIL B 309 306 918 NAF 7120B

TRANSPORT DES MARCHANDISES DANGEREUSES CERTIFICAT D'AGREMENT DE TYPE D'EMBALLAGE

Applicant : CARTOSPE PACKAGING
13, voie Industrielle
60350 ATTICHY FRANCE

N° 7639
Indice 3

REFERENCE DOCUMENTS :

- Road transport : ADR (Part 6), to date in 01/01/2019
- Rail transport : RID (Part 6), to date in 01/01/2019
- Transport by waterway : ADN (Part 6), to date in 01/01/2019
- Maritime transport : IMDG code (Part 6), to date in 01/01/2019
- Air transport : Doc OACI 9284 AN/905 (Part 6), to date in 2017/2019
- UN Recommendations on the transport of dangerous goods - Model Regulations - ST/SG/AC.10/1/Rev.20 - Part 6

Site of conditioning :
Non applicable

DESCRIPTION OF THE TYPE OF PACKAGING (according to information given by the applicant) :

Sample record n° 13207D

- Manufacturer : CARTOSPE PACKAGING , F-60350 Attichy
- Packaging code : 4G
- Type, materials : Caisse , Carton
- Construction method : Collage
- Commercial reference : 50 L BAS VERSION 2015
- Constituent raw material : Carton ondulé DF, Kraft blanc 125 g/m² / Recyclé 120 g/m² / Test 170 g/m², cannelure B, 1.1 selon NF Q 12-008, indice Cobb < 155 g/m²/30'

- Drawings : ft 16662 du 01/10/2014
- Empty weight (tare) : Sans objet
- Overall external dimensions : 0,386 x 0,386 x 0,492 m
- Internal dimensions : 0,380 x 0,280 x 0,48 m
- Minimum thickness : 2,42 mm
- Closures : Rabats supérieurs recouvrants avec languette de fermeture verrouillable

- Handling : 2 poignées prédécoupées sur deux faces opposées en partie haute
- Particularities : Fond automatique.

- Inner arrangement** : Lest constitué de granulés PE dans une sachette en plastique (épaisseur 40 µm, dimensions 692 x 975 mm) collée sur les parois intérieures de la caisse (en partie supérieure) fermée par un lien coulissant incorporé dans la sachette (chignon noué)

AUTHORIZED AREAS OF USE : Dangerous goods solides in the following conditions :

- Packaging group : II,III
- Max. gross weight : 13 kg
- Stacking : Maximal Load : 66 kg

TEST AND MARKING :

Satisfactory test results, according to report : **BVT 172739 indice 0 du 14/12/2009**

Quality assurance plan reference and index : **PAQ 1727-7F-8F-830 indice 1**

Marking model to be placed on the condition that the regulatory measures are met



4G / Y 13 / S / - - *

F / BVT 172739 / CARTOSPE PACKAGING

* See the appendix to the approval certificate

The French text serves as a basis for the translation, and should any difference exist between the French text and a text in another language, the French text will prevail.

Issued in Rungis

Manager of the approved test laboratory

On 24/04/2019 for a period of five years

Mrs E.FRAGU

A copy of this report is sent to the Ministry of Transport.

Ministère chargé des transports terrestres et maritime de matières dangereuses



Bureau de Vérifications Techniques
36 rue du Jura
CS 10398
94633 RUNGIS CEDEX
FRANCE
Tél. +33 (0)1 41 80 59 00

S.A.S au capital de 282 150 € RCS CRETEIL B 309 306 918 NAF 7120B

TRANSPORT DES MARCHANDISES DANGEREUSES CERTIFICAT D'AGREMENT DE TYPE D'EMBALLAGE

Applicant : CARTOSPE PACKAGING
13, voie Industrielle
60350 ATTICHY FRANCE

N° 7653
Indice 2

REFERENCE DOCUMENTS :

- Road transport : ADR (Part 6), to date in 01/01/2019
- Rail transport : RID (Part 6), to date in 01/01/2019
- Transport by waterway : ADN (Part 6), to date in 01/01/2019
- Maritime transport : IMDG code (Part 6), to date in 01/01/2019
- Air transport : Doc OACI 9284 AN/905 (Part 6), to date in 2017/2019
- UN Recommendations on the transport of dangerous goods - Model Regulations - ST/SG/AC.10/1/Rev.20 - Part 6

Site of conditioning :

Non applicable

DESCRIPTION OF THE TYPE OF PACKAGING (according to information given by the applicant) :

Sample record n° 15107A

- Manufacturer : CARTOSPE PACKAGING , F-60350 ATTICHY
- Packaging code : 4G
- Type, materials : Caisse , Carton
- Construction method : Collage
- Commercial reference : 50 L HAUT VERSION 2015
- Constituent raw material : Carton ondulé DF, Kraft blanc 125 g/m² / Recyclé 120 g/m² / Test 170 g/m², cannelure B, 1.1 selon NF Q 12-008, indice Cobb < 155 g/m²/30'

- Drawings : ft 16658 du 29/09/2014
- Empty weight (tare) : 0,54 kg
- Overall external dimensions : 0,300 x 0,300 x 0,585 m
- Internal dimensions : 0,295 x 0,295 x 0,575 m
- Minimum thickness : 2,42 mm
- Closures : Rabats supérieurs recouvrants avec languette de fermeture verrouillable

- Handling : 2 poignées prédécoupées sur deux faces opposées en partie haute
- Particularities : Fond automatique.

Inner arrangement : Lest constitué de granulés PE dans une sachet plastique (épaisseur 40 µm, dimensions 622 x 1059 mm) collée sur les parois intérieures de la caisse (en partie supérieure) et fermée par un lien coulissant incorporé dans la sachet (chignon noué).

AUTHORIZED AREAS OF USE :

Dangerous goods solides in the following conditions :

- Packaging group : II,III
- Max. gross weight : 15 kg
- Stacking : Maximal Load : 62 kg

TEST AND MARKING :

Satisfactory test results, according to report : **BVT 172738 Indice 1 du 13/11/2014**

Quality assurance plan reference and index : **PAQ 1727-7F-8F-830 indice 1**

Marking model to be placed on the condition that the regulatory measures are met



4G / Y 15 / S / - - *

F / BVT 172738 / CARTOSPE PACKAGING

*** See the appendix to the approval certificate**

The French text serves as a basis for the translation, and should any difference exist between the French text and a text in another language, the French text will prevail.

Issued in Rungis

Manager of the approved test laboratory

On 23/04/2019 for a period of five years

Mrs E.FRAGU

A copy of this report is sent to the Ministry of Transport.